# Photoluminescent Vinyl sheet Safety Data Sheet

## **1. PRODUCT IDENTIFICATION**

Commercial product name: Photoluminescent Vinyl

Producer: EVERYLGOW LTD

http://www.everyglow.com E-mail: info@everyglow.com Product Code: LBG-FH Chemical Family: Photoluminescent Polymer of Chlorinated Hydrocarbon Chemical Name: Polyvinyl Chloride + Photoluminescent pigment CAS No: 9002-86-2 Synonyms: Photoluminescent vinyl

#### 2. PRODUCT INGREDIENTS

No. Components CAS No. Percent (%) OSHA PEL 1 PVC 9002-86-2 50 - 80% 2 Photoluminescent pigment 10% - 40% 3 Proprietary Mixtures 10% Not established

# 3. PHYSICAL/CHEMICAL PROPERTIES

Physical Form: Solid Sheet
Color: Yellow-green
Odor: Insignificant
Boiling Point: Not applicable
Melting Point: Not established
Freezing Point: Not applicable
Solubility in Water: None
Specific Gravity: 0.8 - 2.4 (water = 1)
Vapor Density: Not applicable (air = 1)
Evaporation Rate: None (Butyl Acetate = 1)
Vapor Pressure: Not applicable
% Volatile: None
pH: Not applicable
The physical data presented above are typical values and should not be construed as a specification.

# 4. FIRE HAZARD DATA AND FIGHTING METHOD

Flash Point: Not applicable

### **EVERYGLOW LTD**

#### Autoignition: Not applicable

Flammable Limits In Air (LEL, %) Not applicable (UEL, %) Not applicable

#### Extinguishing Media: Dry chemical, foam water, or carbon dioxide

#### **Special Fire Fighting**

**Procedure:** In the event of a fire, wear NIOSH approved, positive pressure, self-contained breathing apparatus (SCBA) and full protective clothing. Evacuate all personnel from danger area. Use dry chemical, foam, water or carbon dioxide to extinguish fire.

#### Unusual Fire and Explosion Hazards:

This product is nonflammable and nonexplosive under normal conditions of use. It will not continue to burn after ignition without an external fire source. When forced to burn, the major gaseous products of the combustion of PVC are carbon monoxide, carbon dioxide, and hydrogen chloride.

## 5. HUMAN HEALTH DATA

Emergency Overview: During a fire emergency, avoid inhalation, eye and skin contacts.
Primary Route(s) of
Exposure: Inhalation, Eye, Skin Contact
Potential Health Effects and Symptoms of Over-Exposure
Eye Contact: Dust may cause eye irritation
Skin Contact: May cause skin irritation
Inhalation: May cause discomfort in nose and throat
Ingestion: Unlikely
Medical Conditions Aggravated by Overexposure:
Available toxicological information and the physical/chemical properties of the
material suggest that there is no evidence that this product aggravates an existing

medical condition.

Carcinogenicity: NTP: No IARC: No OSHA: No

## 6. FIRST AID MEASURES

**Eye Contact:** Immediately flush eyes with water for at least 15 minutes. Do not rub the eyes. If irritation develops, consult a physician.

**Skin Contact:** Wash affected skin areas with soap and water. If irritation develops, get medical attentions immediately

**Inhalation:** Remove subject to fresh air. If symptoms develop, seek immediate medical attention.

Ingestion: Unlikely.

Notes to Physician: Treat symptomatically and supportively.

Other Instructions: Never give anything by mouth to an unconscious person.

### 7. EXPOSURE CONTROLS, PERSONAL PROTECTION RECOMMENDATIONS

**Eye Protection:** Wear safety glasses during sheet cutting or fabricating process

Skin Protection: Wear gloves and long sleeved clothing when cutting or fabricating sheets.

**Respiratory Protection:** Use NIOSH/MAHA approved dust respirators as needed.

Engineering Control: Ventilation Requirements – Local Exhaust

**Required Work/Hygiene** Do not eat, drink, or smoke in work area. Wash hands thoroughly after handling, **Procedure:** especially before eating, drinking, smoking, chewing, or using restroom facility. **Exposure Guidelines:** 

No. Components OSHA-PEL ACGIH-TLV

1 PVC 5 mg/M3 (as respirable dust) 10 mg/M3 (as nuisance dust)

## 8. ACCIDENTAL RELEASE CONTROL MEASURES

Response to Spills: Not applicable

#### 9. HANDLING AND STORAGE

**Handling:** Use with care. Wear gloves if necessary when cutting or fabricating sheet. **Storage:** Store in a cool dry, well-ventilated area away from sources of extreme heat or fire.

Container Use: Not applicable

## **10. STABILITY AND REACTIVITY**

Stability: Stable

Conditions to Avoid: Avoid fire or elevated temperature above 250°C.

Hazardous

**Decomposition:** If burned, it will generate carbon dioxide, carbon monoxide and hydrogen chloride.

Hazardous

Polymerization: Will not occur

# **11. DISPOSAL CONSIDERATIONS**

**Disposal Method:** It must be disposed of in accordance with Federal, State and local environmental control regulations.

Recycle/Reclaim: Recycling of PVC sheet should be encouraged where possible.

## **12. TRANSPORT INFORMATION**

DOT Shipping Name: Not listed DOT Label: Not applicable DOT Hazard Class: Not regulated UN/NA Number: Not applicable Hazard Label(s): Not applicable Hazard Placard(s): Not applicable Packing Group: Not applicable Bulk Packaging: Not applicable RQ: Not applicable Emergency Response Guide (ERG) No.: Not applicable

# **13. TOXICOLOGICAL INFORMATION**

The information provided below can be subject to misinterpretation. Therefore, it is essential that the following information be interpreted by individuals trained in its evaluation.

Chemical Toxicity Data

PVC orl-rat TDLo: 210 g/kg/30W-C:ETA

# 14. ECOLOGICAL INFORMATION

No data is available on the adverse effects of this product on the environment. Neither COD nor BOD data are available.

## **15. REGULATORY INFORMATION**

# FEDERAL REGULATORY INFORMATION

OSHA Status: Not listed EPA Clean Air Act Status: Not listed EPA Clean Water Act Status: Not listed TSCA Status: PVC is listed on TSCA Inventory (40 CFR710) CERCLA RQ: Not listed SARA Title III

PVC Section 302\* Section 313\*\* Section 311/312\*\*\*

None None None

\*Reportable quantity of extremely hazardous substance, Sec. 302

\*Threshold planning quantity, extremely hazardous substance, Sec. 302

\*\*Toxic chemical. Sec. 313

\*\*Category as required by Sec 313 (40CFR372.65C). Must be used on Toxic Release Inventory form.

\*\*\*Hazard category for SARA Sec.311/312 reporting H1=acute health hazard, H2=chronic health hazard, P3=fire hazard,

P4=sudden release of pressure hazard, P5=reactive hazard

RCRA Status: The product is not an RCRA hazardous waste either by listing or by characteristic.

However, under RCRA, it is the responsibility of the product user to determine at the

time of disposal whether a material containing the product or derived from the product

should be classified as a hazardous waste (40CFR261.20-24).

#### OTHER REGULATORY INFORMATION

The following chemicals are specifically listed by individual states; other product-specific health and safety data in other sections of the MSDS may also be applicable for state requirements. For details on your

### **EVERYGLOW LTD**

regulatory requirements, you should contact the appropriate agency in your state. **State Chemical Regulation** Texas PVC Effects Screening Level (ESL) List: short term 50 ug/M<sub>3</sub>; long term 5 ug/M<sub>3</sub> California Proposition 65: warning – this product contains a chemical, residual VCM, known to the state of California to cause cancer **Product Name:** PL Rigid PVC Sheet **International** United Kingdom Occupational Exposure Standards: TWAs total inhalable dust 10 mg/M<sub>3</sub> TWA;

Respirable dust 5mg/M3

Germany MAK Value: fine dusts 5 mg/M3 MAK

#### **16. FURTHER INFORMATION**

This information, which describes our product as to possible security requirements, is based on the present state of our knowledge and experience. It is given in good faith but no warranty, expressed or implied, in respect of the quality and properties of our product is made. We can also provide the test certificate for some items, such as toxicity, ISO9001,2000, which have been shown in our catalogues.